

SPRAY THERMAL BARRIER REQUEST

Spray-applied Cementitious or Intumescent Coating

PROJECT ADDRESS:		BPA/BP #	
Builder Name: _____		Builder Address: _____	
PRODUCT	CCMC Listing or Report # _____ Manufacturer _____ Colour _____	Have the plans, details and specifications been reviewed and sealed by a design professional (Architect or Professional Engineer)? Yes <input type="checkbox"/> No <input type="checkbox"/> _____ _____	PART 3 CONSTRUCTION
PRIMER	Product _____ Thickness (mil WFT) _____	Primer thickness shall be not less than 3 mil wet film thickness (WFT)	PRIMER
COATING	Location of application? _____ _____ _____	Thickness (mil WFT) _____ _____ _____	COATING
SAFETY	Buildings cannot be occupied for 24 hours after the installation of spray-applied thermal barrier. The general contractor is to ensure inspections are booked not less than 24 hours after installation is completed.		
SITE REQUIREMENTS	It is the contractor's responsibility to ensure a label is placed on the job site including the product information and stating: "This certificate indicates that the installed spray-applied thermal barrier has been installed in accordance with the manufacturer's instructions."		
INSTALLER	Installing Company: _____ Certified Installer: _____ Signed by (Print) : _____ Phone Number: _____	Date _____ ID #: _____ Signature: _____ Email Address: _____	